

Greater boiler safety



Specifications – NRGS 15-1

PN 25 / G 1"
1st and 2nd low-level alarm
High-level alarm
Level control
Material: stainless steel
Power supply: 115/230 VAC
Length supplied: 1000 mm



Specifications – LRGS 15-1

PN 25 / G 3/4" (ISO 228-1)
Measuring range:
100 – 10000 mS/cm (25 °C)
(50 – 5000 ppm (25 °C))
MAX TDS alarm
Continuous blowdown control
Material: stainless steel
Power supply: 115/230 VAC
Lengths supplied: 200, 300,
400, 500, 600, 800, 1000 mm



The Benefits of the GESTRA Level Control Electrode

- ▶ Clear visual indication
- ▶ Enhanced safety
- ▶ No maintenance required
- ▶ Simple installation
- ▶ No moving parts
- ▶ Redundancy of tips and relays
- ▶ Same unit for various applications and voltages
- ▶ Prolonged life and operation time
- ▶ Stainless steel body & tips
- ▶ Includes testing features and interlock
- ▶ Extended pressure rating PN 25 / Class 250
- ▶ Enhanced boiler protection and energy efficiency
- ▶ Easy to calibrate and recalibrate
- ▶ CE, UL and FM approvals

See also our
Energy Supp
Visit our ho

GESTRA /

Münchener Str.
P.O. Box 10 54
Telephone +49
Telefax +49
E-mail gesi
Internet ww

w w w . g e s t r a . d e

818443-01/1119 © 21
Printed in Germany - Te